

4MP LightHunter Intelligent Bullet Camera with built in Vario-Lens 8-32mm and Heater

IPC264SA-AHDX4K-I1



Features

- High quality image with 4MP, 1/1.8" CMOS sensor
- 2688*1520@60fps in the main stream, deliver detailed live while 60fps keeping it smooth and closer to the real image
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection
- LightHunter technology ensures ultra-high image quality in low illumination environment
- Up to 130 dB Optical WDR (Wide Dynamic Range)
- 5 mixed-lights, up to 120m IR range, up to 30m warm light
- DC12V or PoE (IEEE 802.3at) power supply
- Built-in heater, allow low temperature start-up at -40° C
- Audio 2 in and 1 out, Alarm 3 in and 2 out
- IP67,IK10
- *Intelligent function supported when frame rate is below 30

Specifications

Camera	Description
Sensor	1/1.8"CMOS
Min. Illumination	Colour:0.001lux (F1.6, AGC ON) 0 lux with Light
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
WDR	130dB
S/N	>56dB
Lens	Description
Lens type	8~32mm
Iris Type	P-iris
Iris	F1.6
Field of View (H)	42.6° ~23.5°
Field of View (V)	15.2° ~8.9°
Field of View (D)	52.4° ~27.7°
DORI	Description
DORI Distance (Lens)	8~32(mm)
DORI Distance (Detect)	165.7m(543.7ft)~444.4m(1458.1ft)
DORI Distance (Observe)	66.3m(217.5ft)~177.8m(583.2ft)
DORI Distance (Recognize)	33.1m(108.7ft)~88.9m(291.6ft)
DORI Distance (Identify)	16.6m(54.4ft)~44.4m(145.8ft)
Illuminator	Description
Illumination Distance(IR)	120m
Illumination Distance (Warm Light)	30m
Wavelength	750nm
IR On/Off Control	Auto/Manual
Video	Description
Video Compression	Ultra 265&H.265&H.264&MJPEG
Frame Rate—Main Stream	4MP(2688*1520),Max 60fps
Frame Rate—Sub Stream	2MP(1920*1080), Max 60fps
Frame Rate—Third Stream	D1 (720*576), Max 60fps
Video Bit Rate	128 Kbps~16 Mbps
ROI	Up to 8 areas

Video stream	Triple streams
OSD	Up to 10 OSDs
Privacy Mask	Up to 8 areas (8 blacks / 8 mosaics)
Image	Description
White Balance	Auto;Outdoor;Fine Tune;Sodium Lamp;Locked;Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Flip Vertical;Flip Horizontal;Normal;180° ;90° Clockwise;90° Anti-clockwise
HLC	Support
BLC	Support
Defog	Digital Defog
Intelligent	Description
Traffic Monitoring	Support capturing car license picture and collect other car information when the car passes tripwire;Up to 4 lanes can be set;Two types of application mode available: High/Low pole
Smart intrusion prevention	Support false alarm filtering: Cross line detection, Intrusion detection, Enter area detection, Leave area detection
People Counting	People counting, support people flow counting and crowd density monitoring(Only Channel 1)
Events	Description
Basic Detection	Motion detection;Audio detection;Tampering alarm
General Function	Watermark;IP Address Filtering;Access Policy;ARP Protection;RTSP Authentication;User Authentication;HTTP authentication;Alarm input;Alarm output
Audio	Description
Audio Compression	G.711U;G.711A
Audio Bitrate	128 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	16KHZ
Storage	Description
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR;NAS(NFS)
Network	Description
Protocols	TLS1.3;SSH;IGMP;RTP;RTCP;SMTP;IPv4;IPv6;ICMP;ARP;TCP;UDP;DHCP;PPPoE;RTSP;RTMP;DNS;DDNS;NTP;FTP;UPnP;HTTP;HTTPS;802.1x;SNMP;QoS;SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T, Profile M);API;SDK
User/Host	Up to 32 users. 3 user levels: administrator,common user and operator
Security	Password protection&Strong password&HTTPS encryption&Export operation logs&Basic and digest authentication for RTSP&Digest authentication for HTTP&TLS 1.2&WSSE and digest authentication for ONVIF
Client	EZStation; EZLive;EZView
Web Browser	Plug-in required live view: IE 10 and above,Chrome 45 and above,Firefox 52 and above,Edge 79 and above&Plug-in free live view: Chrome 57.0 and above,Firefox 58.0

	and above,Edge 16 and above
Pan/Tilt	Description
Home Position	Support
Interface	Description
Audio I/O	2/1
Alarm I/O	3/2
Serial Port	1 channel RS485 interface
Built-in Mic	Built-in two mics
Built-in Speaker	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Certification	Description
EMC	CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Safety	CE LVD (EN 62368-1:2014+A11:2017) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
Protection	IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013) IK10 (IEC 62262:2002)
General	Description
Power	DC12V(±25%) , PoE+ (IEEE 802.3at)
Power Consumption	Max 23W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions	406 x 126 x 130mm(16.0" x 5.0" x 5.1")
Weight	2.14kg(4.72lb)
Working Environment	-40℃ ~ 60℃ (-40° F ~ 140° F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40℃ ~ 70℃ (-40° F ~ 158° F), Humidity: ≤95% RH (non-condensing)
Surge protection	6KV
Reset button	Support
Heater	Support
Web Client Language	22 Languages Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese, Arabic, Slovak

Dimensions

